



January 7, 1998

AXIAL LEADED HERMETICALLY SEALED FAST RECTIFIER DIODE

QUICK REFERENCE DATA

- Low reverse recovery time
- Glass passivated for hermetic sealing
- Low switching losses
- Soft, non-snap off, recovery characteristics
- Avalanche capability

- $V_R = 1000V$
- $I_F = 2.7A$
- $t_{rr} = 150nS$
- $I_R = 5\mu A$

ABSOLUTE MAXIMUM RATINGS (@ 25°C unless otherwise specified)

	Symbol	3PFR0	Unit
Working reverse voltage	$V_{RWM}$	1000	V
Repetitive reverse voltage	$V_{RRM}$	1000	V
Surge reverse voltage	$V_{RSM}$	1100	V
Average forward current (@ 55°C, lead length 0.375")	$I_{F(AV)}$	2.7	A
Repetitive surge current (@ 55°C in free air, lead length 0.375")	$I_{FRM}$	21	A
Non-repetitive surge current ( $t_p = 8.3mS$ , @ $V_R$ & $T_{jmax}$ )	$I_{FSM}$	70	A
Storage temperature range	$T_{STG}$	-65 to +175	°C
Operating temperature range	$T_{OP}$	-65 to +175	°C

MECHANICAL

G83

DIM #	DIMENSIONS				NOTE
	MM		INCHES		
A	-	4.50	-	.177	-
B	28.0	-	1.10	-	-
C	-	5.00	-	.197	-
D	-	1.35	-	.053	-

Weight = 0.04oz



January 7, 1998

**ELECTRICAL CHARACTERISTICS** (@ 25°C unless otherwise specified)

	Symbol	3PFR0	Unit
Average forward current max. (pcb mounted; T <sub>A</sub> = 55°C) for sine wave	I <sub>F(AV)</sub>	1.15	A
for square wave (d = 0.5)	I <sub>F(AV)</sub>	1.20	A
Average forward current max. (T <sub>L</sub> = 55°C; L = 3/8") for sine wave	I <sub>F(AV)</sub>	2.60	A
for square wave	I <sub>F(AV)</sub>	2.70	A
I <sup>2</sup> t for fusing (t = 8.3mS) max.	I <sup>2</sup> t	20	A <sup>2</sup> S
Forward voltage drop max. @ I <sub>F</sub> = 2.0A, T <sub>j</sub> = 25°C	V <sub>F</sub>	1.5	V
Reverse current max. @ V <sub>RWM</sub> , T <sub>j</sub> = 25°C	I <sub>R</sub>	5.0	µA
@ V <sub>RWM</sub> , T <sub>j</sub> = 100°C	I <sub>R</sub>	25	µA
Reverse recovery time max. 0.5A I <sub>F</sub> to 1.0A I <sub>R</sub> . Recovers to 0.25A I <sub>RR</sub> .	t <sub>rr</sub>	150	nS
Junction capacitance typ. @ V <sub>R</sub> = 5V, f = 1MHz	C <sub>j</sub>	70	pF

**THERMAL CHARACTERISTICS**

	Symbol	3PFR0	Unit
Thermal resistance - junction to lead Lead length = 0"	R <sub>θJL</sub>	12	°C/W
Lead length = 0.375"	R <sub>θJL</sub>	26	°C/W
Thermal resistance - junction to amb. on 0.06" thick pcb. 1 oz. copper.	R <sub>θJA</sub>	75	°C/W



January 7, 1998




Fig 1. Forward voltage drop as a function of forward current.




Fig 2. Maximum power versus lead temperature.




Fig 3. Transient thermal impedance characteristic.




Fig 4. Typical junction capacitance as a function of reverse voltage.



January 7, 1998




Fig 5. Forward power dissipation as a function of forward current, for sinusoidal operation.




Fig 6. Forward power dissipation as a function of forward current, for square wave operation.




Fig 7. Typical repetitive forward current as a function of pulse width at 55°C;  $R_{\theta JL} = 22$  °C/W;  $V_{RWM}$  during  $1 - \delta$ .




Fig 8. Typical repetitive forward current as a function of pulse width at 100°C;  $R_{\theta JL} = 75$  °C/W;  $V_{RWM}$  during  $1 - \delta$ .